

Incredible **100,000 hrs**

GENERAL DESCRIPTION

Neptun's 23" Induction flood fixture combines classic form and versatility to make it an excellent choice for new construction or retrofit applications. The 39 series flood fixture is offered in a variety of wattages and mounting options to provide maximum flexibility in all types of applications. It can replace existing HID & HPS fixtures up to 1000W.

APPLICATION

- Parking Lot Lighting
- Car Lot Lighting
- Area & Storage Lighting
- Street Lighting
- Walkway Lighting
- Building Accent Lighting
- Sign / Monument Lighting

STRUCTURE, MATERIALS, & FEATURES

- Heavy-gauge, die-cast aluminum housing.
- Custom designed anodized aluminum reflectors for superior illuminance.
- Heat and impact resistant tempered flat glass lens. (IESNA full-cutoff)
- Integral structural support plate for mounting arm ensures strength.
- Corrosion resistant electrocoat dark bronze finish (custom colors available).
- Hinged aluminum door frame incorporates stainless steel hardware.
- Continuous silicone gasketing surrounds lens for weather - tight seal.
- Inductively coupled rectangular induction bulb.
- High power factor, low THD electronic ballast with surge protection.
- Instant-On flicker-free Cold Start and Hot Re-Start.
- High quality glare-free light with high CRI above (83).
- Bright white light (5000°K) for greater visibility and safety.
- Advance phosphors for high lumen output and high lumen maintenance.
- Up to 20 year maintenance free operation with 10 Year Warranty.

ORDERING INFORMATION

Sample Number: 1R39200-UNV-SF-850-LD-BRZ
 Custom options and accessories available. Please consult factory

Series	Voltage	Mounting	Color Temp	Accessories	Color
1R39200 = 23" Flood - 200W 2R39300 = 23" Flood - 300W* 2R39400 = 23" Flood - 400w* * 2 rectangle lamps.	UNV = 120-277 VAC 347 V = 347 VAC 480 V = 480 VAC	SF = Slip Fitter YK = Yoke Mount Bracket	830 = 3000°K 841 = 4100°K 850 = 5000°K* * Standard	LD = Twist-Lock Photocell MD = Motion Detector FSGS = Front Side Glare Shield	BRZ = Dark Bronze * Custom Colors Available



lightinnovations@work™

PRODUCT INFORMATION

Model No.	Description	Rated Watts	Input Watts	Initial Lumens	Universal Line Voltage (VAC)	Max Line Current (Amp) @ 120 - 277	THD	Power Factor	Weight
1R39200-UNV	23" FLOOD Fixture	200	210	16,000	120-277	1.75-0.75	<10%	0.98	55 lbs
2R39300-UNV*	23" FLOOD Fixture	300	315	24,000	120-277	2.62-1.13	<10%	0.98	60 lbs
2R39400-UNV*	23" FLOOD Fixture	400	420	32,000	120-277	3.50-1.51	<10%	0.98	60 lbs



* Features dual bulbs & ballasts

SPECIFICATIONS

- Ballast Type Electronic
- Start Method InstantON
- Hot Re-start InstantON
- Universal Input Line Voltage 120-277 VAC
- Input Line Frequency 50/60 Hz
- Lamp Operating Frequency 250 kHz
- Ballast Off-State Draw 0 Watts
- Sound Rating Class A
- ANSI Surge Protection Class A
- Lamp / Ballast System Life 100,000 Hrs.
- Lumen Maintenance @75,000Hrs > 70%
- Color Temperature 5000°K
- Color Rendering Index (CRI) > 83
- Minimum Starting Temperature -20°F
- Maximum Starting Temperature 160°F
- Initial Lumens per Watt 80
- Shock / Vibration Resistant Yes
- Power Factor > 0.98
- Total Harmonic Distortion < 10%
- Inrush Current Peak < 10 Amp
- ETL Listed / UL Standard 1598 Yes
- FCC Compliance Part 18, Subp. C
- EPA Rating 1.77
- IP Rating IP65
- Warranty 10 Year



MOUNTING OPTIONS

Slip Fitter (SF)




2-1/2" I.D.
Accepts up to 2-3/8"
Tenon or Pipe

Yoke Bracket (YK)



PHOTOMETRICS (See Complete IES File)



Type V Distribution

Neptun Light, Inc.
13950 Business Center Drive
Lake Forest, IL 60045
Fax: 847.735.8004

Neptun Light, Inc. reserves the right to change materials or modify the design of its product without notification as part of the company's continuing product improvement program.
©2002-2016 Neptun Light, Inc. All rights reserved. Spec. Rev. 4-2016