

Incredible **100,000 hrs**

GENERAL DESCRIPTION

Neptun's Low Profile high/low bay fixtures feature a rugged design to be used in a high ceiling applications. The custom anodized aluminum reflectors are designed to provide maximum illuminance on the intended surface. The LP1 series fixture is offered in a variety of wattages to provide maximum flexibility in a variety of applications. It can replace existing HID & HPS fixtures up to 450W.

APPLICATION

- Warehouse Lighting
- Factory Lighting
- Retail Lighting
- Showroom Lighting
- Grocery Store Lighting
- Tennis Court Lighting
- Gymnasium Lighting

STRUCTURE, MATERIALS, & FEATURES

- Formed stainless steel housing with screwed assembly construction.
- Custom designed anodized aluminum reflectors for superior illuminance.
- Corrosion resistant electrocoat white finish (custom colors available).
- Supplied with Gripple cables for suspended mounting.
- Inductively coupled rectangular induction bulb.
- High power factor, low THD electronic ballast with surge protection.
- Instant-On flicker-free Cold Start and Hot Re-Start.
- High quality glare-free light with high CRI above (83).
- Bright white light (5000°K) for greater visibility and safety.
- Advance phosphors for high lumen output and high lumen maintenance.
- Up to 20 year maintenance free operation.
- 10 Year Warranty.

ORDERING INFORMATION

Sample Number: LP1-080-UNV-850-MD-WG-C3
 Custom options and accessories available. Please consult factory

Series	Wattage	Voltage	Color Temp	Accessories	Options
LP1 = Low Profile High-Bay - 1 Lamp	080 = 80 W 100 = 100 W 120 = 120 W 150 = 150 W 200 = 200 W 250 = 250 W	UNV = 120-277 VAC 347V = 347 VAC 480V = 480 VAC	830 = 3000°K 841 = 4100°K 850 = 5000°K * * Standard	MD = Motion Detector	WG = Wire Guard PL = Polycarbonate Lens C3* = 3' Cord-No Plug (other lengths available by specifying cord length C6 = 6' cord) PC3 = 3' Cord with NEMA Plug (verify plug type when ordering) * Standard



lightinnovations@work™

PRODUCT INFORMATION


Model No.	Description	Rated Watts	Input Watts	Initial Lumens	Universal Line Voltage (VAC)	Max Line Current (Amp) 120 - 277	THD	Power Factor	Weight
LP1080-UNV	1 Lamp Low-Profile Fixture	80	82	6,400	120-277	0.69-0.30	<10%	0.98	25 lbs
LP1100-UNV	1 Lamp Low-Profile Fixture	100	105	8,000	120-277	0.87-0.37	<10%	0.98	25 lbs
LP1120-UNV	1 Lamp Low-Profile Fixture	120	125	9,600	120-277	1.05-0.45	<10%	0.98	25 lbs
LP1150-UNV	1 Lamp Low-Profile Fixture	150	158	12,000	120-277	1.31-0.56	<10%	0.98	25 lbs
LP1200-UNV	1 Lamp Low-Profile Fixture	200	210	16,000	120-277	1.75-0.75	<10%	0.98	25 lbs
LP1250-UNV	1 Lamp Low-Profile Fixture	250	265	20,000	120-277	2.18-0.94	<10%	0.98	25 lbs

SPECIFICATIONS

- Ballast Type Electronic
- Start Method InstantON
- Hot Re-start InstantON
- Universal Input Line Voltage 120-277 VAC
- Input Line Frequency 50/60 Hz
- Lamp Operating Frequency 250 kHz
- Ballast Off-State Draw 0 Watts
- Sound Rating Class A
- Lamp / Ballast System Life 100,000 Hrs.
- Lumen Maintenance @75,000Hrs > 70%
- Color Temperature 5000°K
- Color Rendering Index (CRI) 83
- Minimum Starting Temperature -20°F
- Maximum Starting Temperature 160°F
- Lumens per Watt 80
- Shock / Vibration Resistant Yes
- Power Factor > 0.98
- Total Harmonic Distortion < 10%
- Inrush Current Peak < 10 Amp
- ETL Listed / UL Standard 1598 Yes
- FCC Compliance Part 18, Subp. C
- IP Rating IP43
- Warranty 10 Year


MOUNTING OPTIONS

Hanging Mount



Supplied with Gripple Hangers

PHOTOMETRICS (See Complete IES File)



Type V Distribution

Neptun Light, Inc.
 13950 Business Center Drive
 Lake Forest, IL 60045
 Fax: 847.735.8004

Neptun Light, Inc. reserves the right to change materials or modify the design of its product without notification as part of the company's continuing product improvement program.
 ©2002-2016 Neptun Light, Inc. All rights reserved. Spec. Rev. 4-2016