

SOLAR LIGHTING SYSTEM

LFP BATTERY SYSTEM W/ 90W LIGHTING FIXTURE

Battery System



Polycrystaline Solar Panel Polycrystaline Solar Panel Polycrystaline Solar Panel Solar Panel Polycrystaline Solar Panel Solar Panel Lithium Iron Phosphate

Incredible OFF GRID Operation

GENERAL DESCRIPTION

Neptun's LFP Solar Lighting Systems feature a long life, fully rechargeable unit that allows for complete OFF GRID operation. The exceptional storage system allows for up to 3 Days Autonomy / use without a single recharge. Neptun's solar lighting systems are ideal solutions for areas where electricity is unavailable or you need to eliminate many of the high costs associated with standard lighting installations.

APPLICATION

- · Street & Area Lighting
- · Billboard & Sign Lighting
- · Flood Lighting
- · Building Accent Lighting
- · Park Lighting
- · Security Lighting

STRUCTURE, MATERIALS, & FEATURES

- · 90W High Output Neptun LED fixture of your choice.
- · Battery enclosure with die-cast aluminum housing and mounting system.
- · 180Ah LFP (Lithium Iron Phosphate) battery with 5,000 cycles estimated life.
- · High efficency driver & MPPT charge controller supplied with fixture.
- · 300W Polycrystalline Solar Panel with slip-fitter mounting brackets.
- Corrosion resistant electrocoat finish (custom colors available).
 All enclosures and mounting systems feature stainless steel hardware.
- · Square or Round pole mounting brackets included.
- 5 Year Warranty on complete system
- · Compatible with any Neptun LED 24VDC lighting fixtures.

ORDERING INFORMATION

Sample Number: LED-XXX-24VDC-NE-SLR90-LFP-24VDC-RPM-GRY Custom options and accessories available. Please consult factory

Fixture	System	Battery Mounting	Color
			_
LED-XXX090-24VDC = Choose any 90W Fixture from Neptun's outdoor or indoor catalog or multiple fixtures totaling 90W	NE-SLR90-LFP-24VDC = Solar System for 90W LED fixture. * Includes 300W PPV Solar Panel, 180Ah 24VDC LFP Battery system, all mounting hardware, and wiring	RPM = Round Pole Mount SQPM = Square Pole Mount FSM = Free Standing Ground Mount (for flood, billboard, or wall mounting applications)	GRY = Grey BRZ = Bronze ** Custom Colors Available



lightinnovations@work™



SOLAR LIGHTING SYSTEM

LFP BATTERY SYSTEM W/ 90W LIGHTING FIXTURE

FIXTURE SPECIFICATIONS Choose Any Neptun LED Fixture

Type:	LED (See product sheet for full specification)	
Wattage:	90W	
Projected (L70) @ 25°C:	> 100,000 hrs.	
Lumens per Watt :	> 100	
Input Line Voltage :	24 vdc	
Max Line Current :	3.93A	

CHARGE CONTROLLER SPECIFICATIONS

Type:	Programmable Intelligent MPPT (Included in fixture)
Voltage:	12 vdc or 24 vdc
Output Current :	2400mA
Overvoltage Protection :	(24V) 32.0V
Efficiency of Constant Current :	90% ~ 96%
Operating Temp. :	-40°C ~ +70°C
IP Rating :	IP68

BATTERY SPECIFICATIONS

Battery Type:	Sealed Lithium Iron Phosphate (LFP)	
Weight:	210 lbs. (includes enclosure and mounting arm)	
Dimensions :	(Pole) 13.00"L x 10.00"W x 28.00"H (Gnd.) 25.00"L x 9.50"W x 13.50"H	
EPA Rating :	2.43 ft. ²	
Design Life :	15 Years (5,000 cycles)	
Usage:	Solar / Wind System	
Maintenance :	Maintenance Free	
Nominal Capacity :	180Ah	
Voltage :	24 vdc	
Discharge Cutoff:	Auto @ 20% Capacity	
Charge Operating Temp. :	0°C ~ 45°C	
Storage Temp. :	-20°C ~ 55°C	
Storage Humidity :	< 85%	
UL Standard 1703 :	Yes	
Warranty :	5 Years	

SOLAR PANEL SPECIFICATIONS

SOLAR PAREL SI ECH ICATIONS			
Type:	Polycrystaline - Low-iron solar glass front panel w/ anti-reflective surface		
Cell Arrangement :	60 (6 x 10)		
Wattage :	300w		
Frame :	Silver Anodized Aluminum Alloy		
Mounting:	Adjustable Slip Fitter		
Weight:	75 lbs. (including mounting brackets)		
Dimensions:	39.25"L x 2.00"W x 77.50"H		
Operating Module Temp. :	-40°C ~ +85°C		
Positive Power Tolerance :	0 ~ +5w		
Nominal Power (WP) :	≥ 300w		
Voltage @ Normal Power :	45.1V		
Current @ Normal Power :	8.94A		
Open-Circuit Voltage :	35.2V		
Short-Circuit Current :	8.52A		
Maximum System Voltage :	600 vdc		
Maximum Reverse Current :	15A		
Module Efficiency :	15.3%		
EPA Rating :	16.8 ft. ²		
Product Warranty :	10 Year		
Performance Warranty :	25 Year @ 80% output		

Neptun Light, Inc. 13950 Business Center Drive Lake Forest, IL 60045 Fax: 847.735.8004

Area Lighting



Facade Lighting



Security Lighting



Street Lighting



Flood Lighting



Billboard Lighting



Pole Mount (RPM/SPM)




Ground Mount



PPV Solar Panel



Back View



Adjustable Slip Fitter

Neptun Light, Inc. reserves the right to change materials or modify the design of its product without notification as part of the company's continuing product improvement program.

©2002-2013 Neptun Light, Inc. All rights reserved.

Spec. Rev. 10-2015