
STREET LIGHT / COBRA HEAD FIXTURE



FRIENDLY

Not all products are qualified on the DLC QPL. To view our DLC qualified products, $please\ consult\ the\ DLC\ Qualified\ Products\ List\ at\ www.designlights.org/qpl$





Incredible 100,000 hrs

GENERAL DESCRIPTION

Neptun's Street Light fixtures combine architectural form and versatility to make it an excellent choice for new construction or retrofit applications. The LED-81-L2 series fixture is offered in a variety of wattages to provide maximum flexibility in all types of applications. Custom engineered Type III Asymetrical optics provide excellent uniformity and efficiency. It can replace existing HID & HPS fixtures up

APPLICATION

- Street Lighting
- Pathway Lighting
- Parking Lot Lighting
- Security Lighting
- Storage Area Lighting

STRUCTURE, MATERIALS, & FEATURES

- · Heavy-gauge, die-cast aluminum housing with webbed cooling design.
- Corrosion resistant electrocoat grey finish (custom colors available).
- Slim, state of the art, low profile design for minimum wind load resistance.
- Continuous silicone gasket surrounds lens for IP68 weather tight seal.
- Correlated Color Temperature of (5000°K) for greater visibility and safety.
- 2 COB High Output LED's.
- · Driver with built in Neptun Surge Protective Device (NSPD) provides single phase protection for Line/Neutral, Line/Ground, and Neutral/Ground in accordance with IEEE C62.41 C High (10kV & 10kA).
- InstantON flicker-free Cold Start and Hot Re-Start.
- Up to 15 years Maintenance free operation.
- 10 Year Warranty on complete fixture. (LED's, Driver, & Housing)
- Optional: 0-10V Dimming, Bi-Level Dimming, Wi-Fi Control, Remote Monitoring and ON/ OFF Control, DC 24V Operation - Solar Compatible

ORDERING INFORMATION

Sample Number: LED-81100-L2-UNV-0-10VDIM-850-LD-GRY Custom options and accessories available. Please consult factory

Series	Wattage	Voltage	Options	Color Temp	Accessories	Color	
					-	-	
LED-81 = Street Light	100-L2 = 100 W 120-L2 = 120 W	UNV = 120-277 VAC 347V = 347 VAC 480V = 480 VAC 24VDC = 24V DC	0-10VDIM = 0-10V Dimming BL-DIM = Bi-Level Dimming * * Includes Motion Sensor ** Contact factory for dimming options	835 = 3500°K 841 = 4100°K 850 = 5000°K* * Standard	LD = Light Sensor/Photocell NEMA Twistlock MD = Motion Sensor ON/OFF LGN = Light Genie Node ** ** Contact factory for product Information	GRY = Grey * Custom Colors Available	





lightinnovations@work™







PRODUCT INFORMATION


Model No.	Description	Rated Watts	Input Watts	Initial Lumens	Universal Line Voltage (VAC)	Max Line Current (Amp) 120 - 277	THD	Power Factor	Weight
LED-81100-L2-UNV	LED Street Light Fixture	100	102	11,000	120-277	0.87 - 0.37	<20%	>0.90	16 lbs
LED-81120-L2-UNV	LED Street Light Fixture	120	122	13,200	120-277	1.05 - 0.45	<20%	>0.90	16 lbs

SPECIFICATIONS


	Driver	Constant Current
•	Start Method	.InstantON
•	Hot Re-start	InstantON
•	Power Supply	350mA
•	Driver UL Rating	.Class 1
•	Driver UL Outdoor Rated	.Wet Location
•	Sound Rating	.Class A
•	ANSI Surge Protection	
•	Current Crest Factor	
•	Load Regulation: 5% output current variation	across load range
•	Line Regulation: 1% output voltage variation a	cross voltage range
•	Driver Off-State Draw	.0 Watts
•	Vibration Compliance	.3G
•	Universal Input Line Voltage	.120-277 VAC
•	Input Line Frequency	
•	Projected (L70) @ 25°C	.> 100,000 hrs.

	Color Temperature	5,000°K
٠	Color Rendering Index (CRI)	>80
	Minimum Starting Temperature	
	Maximum Starting Temperature	
	Lumens per Watt	
	Shock / Vibration Resistant	Yes
	Power Factor	
	Total Harmonic Distortion	
	Inrush Current Peak	
	FCC Compliance	
	ETL Listed / UL Standard 1598	
	EPA Rating	
	Housing IP Rating	
	Driver IP Rating	
	Optics IP Rating	
	Warranty	
	,	

MOUNTING OPTIONS



PHOTOMETRICS (See Complete IES File)



TYPE III ASYMMETRICAL

Neptun Light, Inc. 13950 Business Center Drive Lake Forest, IL 60045 Fax: 847.735.8004

Neptun Light, Inc. reserves the right to change materials or modify the design of its product without notification as part of the company's continuing product improvement program.

©2002-2013 Neptun Light, Inc. All rights reserved. Spec. Rev. 4-2015