


### 24VDC OPERATION



## Incredible OFF GRID Operation

### GENERAL DESCRIPTION

Neptun's Security Light Fixture is suitable for a variety of outdoor applications. The 20 series Security Light is offered in a several wattages and features an integrated photocell for Dusk-to-Dawn On/Off control. The 24 Volt DC driver allows for compatible use with Solar or Wind powered systems. It can replace existing HID fixtures up to 175W.

### APPLICATION

- Solar Street Lighting
- Solar Alley Lighting
- Solar Work Yard Lighting
- Solar Parking Lot Lighting
- Solar Security Lighting
- Solar Barn Lighting
- Solar Area Lighting
- Solar Walkway Lighting

### STRUCTURE, MATERIALS, & FEATURES

- Heavy-gauge, die-cast aluminum housing.
- Custom designed anodized aluminum reflectors for superior illuminance.
- Heat and impact resistant, UV protected, non yellowing lens.
- Corrosion resistant electrocoat grey finish (custom colors available).
- Slip Fitter mount accepts 1-1/4" - 2" Round Pipe or Tenon.
- Inductively coupled U-Type Induction bulb.
- High power factor, 24 Volt DC ballast.
- NEMA Photocell for Dusk-to-Dawn On/Off control included.
- Instant-On flicker-free Cold Start and Hot Re-Start.
- High quality glare-free light with high CRI above (83).
- Bright white light (5000°K) for greater visibility and safety.
- Advance phosphors for high lumen output and high lumen maintenance.
- Up to 20 year maintenance free operation.
- 10 Year Warranty.

### ORDERING INFORMATION

Sample Number: 20050-24VDC-850-GRY  
 Custom options and accessories available. Please consult factory

Series	Lamp Wattage	Voltage	Color Temp	Color
20 = Security Light	050 = 50 W 065 = 65 W 080 = 80 W	24VDC = 24 VDC	830 = 3000°K 841 = 4100°K 850 = 5000°K* * Standard	GRY = Gray * Custom Colors Available



### PRODUCT INFORMATION

Model No.	Description	Rated Watts	Input Watts	Initial Lumens	Input Line Voltage (VDC)	Max Line Current (Amp)	Power Factor	Weight
20050-24VDC	Security Light Fixture	50	52	4,000	24	2.18	0.98	8 lbs
20065-24VDC	Security Light Fixture	65	67	5,200	24	2.84	0.98	8 lbs
20080-24VDC	Security Light Fixture	80	82	6,400	24	3.49	0.98	8 lbs

### SPECIFICATIONS

- Ballast Type ..... Electronic
- Start Method ..... InstantON
- Hot Re-start ..... InstantON
- Input Line Voltage ..... 24 VDC
- Input Line Frequency ..... 50/60 Hz
- Lamp Operating Frequency ..... 250 kHz
- Ballast Off-State Draw ..... 0 Watts
- Sound Rating ..... Class A
- Lamp / Ballast System Life ..... 100,000 Hrs.
- Lumen Maintenance @75,000Hrs ..... > 70%
- Color Temperature ..... 5000°K
- Color Rendering Index (CRI) ..... > 83
- Minimum Starting Temperature ..... -20°F
- Maximum Starting Temperature ..... 160°F
- Initial Lumens per Watt ..... 80
- Shock / Vibration Resistant ..... Yes
- Power Factor ..... > 0.98
- ETL Listed / UL Standard 1598 ..... Yes
- FCC Compliance ..... Part 18, Subp. C
- IP Rating ..... IP55
- Warranty ..... 10 Year

### MOUNTING OPTIONS

Pole Mount




Accepts 1-1/4" - 2" Round Tenon or Pole  
(Hardware included)

Wall Mount



(Hardware Not included)

### PHOTOMETRICS (See Complete IES File)



Type V Distribution

Neptun Light, Inc.  
13950 Business Center Drive  
Lake Forest, IL 60045  
Fax: 847.735.8004

Neptun Light, Inc. reserves the right to change materials or modify the design of its product without notification as part of the company's continuing product improvement program.  
©2002-2013 Neptun Light, Inc. All rights reserved.

Spec. Rev. 1-2013