




**UP TO 75%
ENERGY SAVINGS**



Product Dimensions

Wattage	E40 (L)	Width (W)
40W	7.875 in.	4.75 in.
60W	7.875 in.	4.75 in.

Incredible 50,000 hrs

GENERAL DESCRIPTION

Neptun's LED retrofit lamp is designed for use in a variety of applications to replace existing HID or HPS lamps. The LED-348 series retrofit lamp features excellent optics for increased visibility and security with a 360° light engine to evenly illuminate area. Offered in a variety of color temperatures to closely resemble HID or HPS style bulbs. Can replace existing HID & HPS lamps up to 175 Watts.

APPLICATION

- Decorative Post Top Fixtures
- Decorative Acorn Fixtures

STRUCTURE, MATERIALS, & FEATURES

- Cast aluminum heat sink.
- High efficiency, heat and impact resistant, UV protected, non yellowing polycarbonate lens / refractor.
- Internally driven (self-ballasted) driver for easy installation.
- High Output LED's.
- High power factor, low THD driver.
- Instant-On flicker-free Cold Start and Hot Re-Start.
- Bright white light (5000°K) for greater visibility and safety.
- LED engine design with Advanced Thermal Management.
- Up to 15 year maintenance free operation.
- 5 Year Warranty.

ORDERING INFORMATION

Sample Number: LED-348040-UNV-850-E40
Custom options and accessories available. Please consult factory

Source	Series	Wattage	Voltage	Color Temp	Base
LED = LED	348 = Retrofit Lamp	040 = 40 W 060 = 60 W	UNV = 120-277 VAC	830 = 3000°K 841 = 4100°K 850 = 5000°K	E40 = Mogul Base



lightinnovations@work™

PRODUCT INFORMATION

Model No.	Description	Rated Watts	Input Watts	Delivered Lumens	Universal Line Voltage (VAC)	Max Line Current (Amp) @ 120 - 277	THD	Power Factor	Weight
LED-348040-UNV	LED Retrofit Lamp	40	41	4,000	120-277	0.34 - 0.15	<20%	>0.90	1.25 lb
LED-348060-UNV	LED Retrofit Lamp	60	61	6,000	120-277	0.52 - 0.23	<20%	>0.90	1.25 lb

SPECIFICATIONS

- LED Driver Constant Current
- Power Supply 350mA
- Start Method InstantON
- Hot Re-start InstantON
- Universal Input Line Voltage 120-277 VAC
- Input Line Frequency 50/60 Hz
- Driver Off-State Draw 0 Watts
- Sound Rating Class A
- Projected (L70) @ 85°C > 50,000 hrs.
- Color Temperature 3000°K, 4100°K, 5000°K
- Color Rendering Index (CRI) > 80
- Minimum Starting Temperature -40°C
- Maximum Starting Temperature 50°C
- Lumens per Watt > 100
- Shock / Vibration Resistant Yes
- Power Factor > 0.90
- Total Harmonic Distortion < 20%
- Inrush Current Peak < 10 Amp
- FCC Compliance Part 15, Subp. C
- Warranty 5 Year

RECOMMENDED APPLICATION FIXTURES



- * Suitable for Base Down Mounting only
- * 2" (inch) spacing between housing and lamp
- * Contact Factory for Application Verification.

MOUNTING OPTIONS



Base Down

Neptun Light, Inc.
 13950 Business Center Drive
 Lake Forest, IL 60045
 Fax: 847.735.8004

Neptun Light, Inc. reserves the right to change materials or modify the design of its product without notification as part of the company's continuing product improvement program.
 ©2002-2016 Neptun Light, Inc. All rights reserved. Spec. Rev. 7-2016