

# SOLAR LIGHTING SYSTEM GEL BATTERY SYSTEM W/ 90W LIGHTING FIXTURE



#### **Choose Any Neptun LED Fixture**



## **GENERAL DESCRIPTION**

Neptun's GEL Solar Lighting Systems feature a long life, fully rechargeable unit that allows for complete OFF GRID operation. The exceptional storage system allows for up to 3 Days Autonomy / use without a single recharge. Neptun's solar lighting systems are ideal solutions for areas where electricity is unavailable or you need to eliminate many of the high costs associated with standard lighting installations.

## APPLICATION

- Street & Area Lighting
- Billboard & Sign Lighting
- Flood Lighting
- Building Accent Lighting
- Park Lighting
- Security Lighting

## **ORDERING INFORMATION**

STRUCTURE, MATERIALS, & FEATURES

- 90W High Output Neptun LED fixture of your choice.
- · Battery enclosure with die-cast aluminum housing and mounting system.
- (2) 150Ah 12VDC GEL battery (24VDC) with 1,500 cycles estimated life.
- High efficency driver & MPPT charge controller supplied with fixture.
- 300W Polycrystalline Solar Panel with slip-fitter mounting brackets.
- Corrosion resistant electrocoat finish (custom colors available).
- All enclosures and mounting systems feature stainless steel hardware.
- $\cdot$  Square or Round pole mounting brackets included.
- $\cdot$   $\,$  2 Year Warranty on complete system
- Compatible with any Neptun LED 24VDC lighting fixtures.

Sample Number: LED-XXX-24VDC-NE-SLR90-GEL-24VDC-RPM-GRY Custom options and accessories available. Please consult factory

Fixture	System	Battery Mounting	Color
-		-	
<b>LED-XXX090-24VDC</b> = Choose any 90W Fixture from Neptun's outdoor or indoor catalog or multiple fixtures totaling 90W	<b>NE-SLR90-GEL-24VDC</b> = Solar System for 90W LED fixture. * Includes 300W PPV Solar Panel, (2) 150Ah 12VDC (total 24VDC) GEL Batteries , all mounting hardware, and wiring	<b>RPM</b> = Round Pole Mount <b>SQPM</b> = Square Pole Mount <b>FSM</b> = Free Standing Ground Mount (for flood, billboard, or wall mounting applications)	GRY = Grey BRZ = Bronze ** Custom Colors Available



# *lightinnovations@work*™

service@neptunlight.com

www.NeptunLight.com

888.735.8330

# 

# SOLAR LIGHTING SYSTEM GEL BATTERY SYSTEM W/ 90W LIGHTING FIXTURE

## FIXTURE SPECIFICATIONS Choose Any Neptun LED Fixture

Type :	LED (See product sheet for full specification)	
Wattage:	90W	
Projected (L70) @ 25°C :	> 100,000 hrs.	
Lumens per Watt :	> 100	
Input Line Voltage :	24 vdc	
Max Line Current :	3.93A	

#### CHARGE CONTROLLER SPECIFICATIONS

Type :	Programmable Intelligent MPPT (Included in fixture)
Voltage:	12 vdc or 24 vdc
Output Current :	2400mA
Overvoltage Protection :	(24V) 32.0V
Efficiency of Constant Current :	90% ~ 96%
Operating Temp. :	-40°C ~ +70°C
IP Rating :	IP68

#### **BATTERY SPECIFICATIONS**

Sealed GEL
220 lbs. (includes enclosure and mounting arm)
(Pole) 13.00"L x 10.00"W x 28.00"H (Gnd.) 25.00"L x 9.50"W x 13.50"H
2.43 ft. <sup>2</sup>
5 Years (1,500 cycles)
Solar / Wind System
Maintenance Free
150Ah
2 @ 12 vdc = 24VDC
Auto @ 20% Capacity
-20°C ~ +45°C
-20°C ~ 55°C
< 85%
BCI / IEC Test Standards
2 Years



#### Facade Lighting





Street Lighting

#### Flood Lighting



#### **Billboard Lighting**



Security Lighting



#### Pole Mount (RPM/SPM)


Ground Mount (FSM)






#### SOLAR PANEL SPECIFICATIONS

Type :	Polycrystaline - Low-iron solar glass front panel w/ anti-reflective surface
Cell Arrangement :	60 (6 x 10)
Wattage :	300w
Frame :	Silver Anodized Aluminum Alloy
Mounting :	Adjustable Slip Fitter
Weight :	75 lbs. (including mounting brackets)
Dimensions :	39.25"L x 2.00"W x 77.50"H
Operating Module Temp. :	-40°C ~ +85°C
Positive Power Tolerance :	0 ~ +5w
Nominal Power (WP) :	≥ 300w
Voltage @ Normal Power :	45.1V
Current @ Normal Power :	8.94A
Open-Circuit Voltage :	35.2V
Short-Circuit Current :	8.52A
Maximum System Voltage :	600 vdc
Maximum Reverse Current :	15A
Module Efficiency :	15.3%
EPA Rating :	16.8 ft. <sup>2</sup>
Product Warranty :	10 Year
Performance Warranty :	25 Year @ 80% output







Adjustable Slip Fitter

Neptun Light, Inc. 13950 Business Center Drive Lake Forest, IL 60045 Fax: 847.735.8004

Neptun Light, Inc. reserves the right to change materials or modify the design of its product without notification as part of the company's continuing product improvement program. ©2002-2013 Neptun Light, Inc. All rights reserved. Spec. Rev. 10-2015

service@neptunlight.com

#### www.NeptunLight.com

888.735.8330