


SOLAR LIGHTING SYSTEM GEL BATTERY SYSTEM W/ 70W LIGHTING FIXTURE



Choose Any Neptun LED Fixture



GENERAL DESCRIPTION

Neptun's GEL Solar Lighting Systems feature a long life, fully rechargeable unit that allows for complete OFF GRID operation. The exceptional storage system allows for up to 3 Days Autonomy / use without a single recharge. Neptun's solar lighting systems are ideal solutions for areas where electricity is unavailable or you need to eliminate many of the high costs associated with standard lighting installations.

APPLICATION

- Street & Area Lighting
- Billboard & Sign Lighting
- Flood Lighting
- Building Accent Lighting
- Park Lighting
- Security Lighting

ORDERING INFORMATION

STRUCTURE, MATERIALS, & FEATURES

- · 70W High Output Neptun LED fixture of your choice.
- Battery enclosure with die-cast aluminum housing and mounting system.
- \cdot (2) 100Ah 12VDC GEL battery (24VDC) with 1,500 cycles estimated life.
- High efficency driver & MPPT charge controller supplied with fixture.
- 250W Polycrystalline Solar Panel with slip-fitter mounting brackets.
- Corrosion resistant electrocoat finish (custom colors available).
- All enclosures and mounting systems feature stainless steel hardware.
- Square or Round pole mounting brackets included.
- \cdot $\,$ 2 Year Warranty on complete system
- Compatible with any Neptun LED 24VDC lighting fixtures.

Sample Number: LED-XXX-24VDC-NE-SLR70-GEL-24VDC-RPM-GRY Custom options and accessories available. Please consult factory

Fixture	System	Battery Mounting	Color
-		-	
LED-XXX070-24VDC = Choose any 70W Fixture from Neptun's outdoor or indoor catalog or multiple fixtures totaling 70W	NE-SLR70-GEL-24VDC = Solar System for 70W LED fixture. * Includes 250W PPV Solar Panel, (2) 100Ah 12VDC (total 24VDC) GEL Batteries , all mounting hardware, and wiring	RPM = Round Pole Mount SQPM = Square Pole Mount FSM = Free Standing Ground Mount (for flood, billboard, or wall mounting applications)	GRY = Grey BRZ = Bronze ** Custom Colors Available



lightinnovations@work™

service@neptunlight.com

www.NeptunLight.com

888.735.8330

NEPTUN

SOLAR LIGHTING SYSTEM GEL BATTERY SYSTE W/ 70W LIGHTING FIXTUR

FIXTURE SPECIFICATIONS Choose Any Neptun LED Fixture

Type :	LED (See product sheet for full specification)	
Wattage:	70W	
Projected (L70) @ 25°C :	> 100,000 hrs.	
Lumens per Watt :	> 100	
Input Line Voltage :	24 vdc	
Max Line Current :	3.06A	

CHARGE CONTROLLER SPECIFICATIONS

Type :	Programmable Intelligent MPPT (Included in fixture)
Voltage:	12 vdc or 24 vdc
Output Current :	2400mA
Overvoltage Protection :	(24V) 32.0V
Efficiency of Constant Current :	90% ~ 96%
Operating Temp. :	-40°C ~ +70°C
IP Rating :	IP68

BATTERY SPECIFICATIONS

Sealed GEL
180 lbs. (includes enclosure and mounting arm)
(Pole) 12.75"L x 9.00"W x 22.50"H (Gnd.) 25.00"L x 9.50"W x 13.50"H
2.0 ft. ²
5 Years (1,500 cycles)
Solar / Wind System
Maintenance Free
100Ah
2 @ 12 vdc = 24VDC
Auto @ 20% Capacity
-20°C ~ +45°C
-20°C ~ 55°C
< 85%
BCI / IEC Test Standards
2 Years



Facade Lighting



Security Lighting



Street Lighting

Flood Lighting



Billboard Lighting





Pole Mount (RPM/SPM)


Ground Mount (FSM)






SOLAR PANEL SPECIFICATIONS

Type :	Polycrystaline - Low-iron solar glass front panel w/ anti-reflective surface
Cell Arrangement :	60 (6 x 10)
Wattage :	250w
Frame :	Silver Anodized Aluminum Alloy
Mounting :	Adjustable Slip Fitter
Weight :	65 lbs. (including mounting brackets)
Dimensions :	39.25"L x 2.00"W x 66.50"H
Operating Module Temp. :	-40°C ~ +85°C
Positive Power Tolerance :	0 ~ +5w
Nominal Power (WP) :	≥ 250w
Voltage @ Normal Power :	30.8V
Current @ Normal Power :	8.14A
Open-Circuit Voltage :	37.5V
Short-Circuit Current :	8.67A
Maximum System Voltage :	600 vdc
Maximum Reverse Current :	15A
Module Efficiency :	15.05%
EPA Rating :	16.8 ft. ²
Product Warranty :	10 Year
Performance Warranty :	25 Year @ 80% output







Adjustable Slip Fitter

13950 Business Center Drive Neptun Light, Inc. reserves the right to change materials or modify the design of its product Lake Forest, IL 60045 without notification as part of the company's continuing product improvement program. ©2002-2013 Neptun Light, Inc. All rights reserved.

service@neptunlight.com

Neptun Light, Inc.

Fax: 847.735.8004

www.NeptunLight.com

888.735.8330

Spec. Rev. 10-2015